

Product quality		
Formats		1522 x 225 x 6 mm
Packaging	Pack:	6 elements / 2.055 m ² / 20.726 kg
	Pallet:	39 packs / 80.133 m ² / 853.31 kg

Tolerances (Requirement EN 16511:2014)		
Squareness of the elements ($\leq 0.20\text{mm}$)		$\leq 0,15\text{ mm}$
Determination of Linearity ($\leq 0.30\text{ mm/m}$)		$\leq 0,20\text{ mm/m}$
Flatness concave / convex	lengthwise ($\leq 0.50/\leq 1.0\%$)	$\leq 0,30/\leq 0,50\%$
	wide ($\leq 0.15/\leq 0.20\%$)	$\leq 0,10/\leq 0,15\%$
Surface flushness	(average $\leq 0.10\text{ mm}$)	(average $\leq 0.10\text{ mm}$)
	(max. $\leq 0.15\text{ mm}$)	(max. $\leq 0.15\text{ mm}$)
Opening between installed elements	(average $\leq 0.15\text{ mm}$)	(average $\leq 0,05\text{ mm}$)
	(max. $\leq 0.20\text{ mm}$)	(max. $\leq 0.10\text{ mm}$)

Guarantee (according Parador guarantee conditions)		Notes
Domestic area	Commercial area	- suitable for all-over adhesion (see notes in our advisor)
Lifetime	10 years	- cleaning an maintenance see instructions - technical changes reserved



Classification		
	Test method	Rating
Utility class 23 domestic areas with intensive use	EN 16511	Living room, hall, kitchen, home office
Utility class 33 commercial areas with intensive use	EN 16511	Classrooms, open-plan offices, shops
Wear layer	ISO 24340	0,55 mm
	Surface Coating	PUR
Reaction to fire	EN 13501-1	B _f -s1
Slip resistance	EN 13893 EN 14041	$\mu \geq 0,30$ DS
Staining resistance	EN 438-2	Category 1 + 2: level 5, no visible change Category 3: level 4, slight change
Light fastness	EN ISO 105 - B02	Blue wool scale: Stage ≥ 6
Resistance to roller castor chairs	EN 425	Type W, no visible changes
Thermal resistance Suitable for installation over underfloor heating when using an appropriate moisture barrier.	EN 12667	0,029 m ² *K/W
Moving a furniture leg	EN 424	No visible changes
Indentation-residual	EN ISO 24343-1	$\leq 0,10\text{ mm}$
Acoustical - Impact noise reduction	EN ISO 10140	17 dB
Length- and Square separating force	ISO 24334	lengthwise $\geq 4\text{ KN/m}$ transversely $\geq 3\text{ KN/m}$
Abrasion	prEN 15468 Annex A	$> 5.000\text{ rev.}$
Dimensional stability	EN ISO 23999	$\leq 0,20\%$
	Micro scratch resistance	EN 16094
	Antimicrobial activity	ISO 22196
	Slip resistance on an inclined plane	DIN 51130
	Disposal	EAK-Code-number
Suitable for damp rooms: 100% waterproof product construction enables use in damp rooms (please observe installation instructions).		20 01 39

Changed:	QMB Parador	File:	PA_TDS_Designboden_Vinyl_Trendime-8_EN_20210801
Date:	15.12.2018	Latest update at:	https://parador.de/en/partner/downloads/index/cat/11/
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			01.08.2021